

# THE SHADE STORE® MOUNTING REQUIREMENTS

## Roman Shades (All Styles)

PRODUCT	DUSTBOARD SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT**	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS		OM ADDITIONS
with cord lock	1¾"	¾"	1½"	2½"	-⅜"		n/a
with continuous loop control	2¼"	1"	2⅜"	3"	-⅜"		n/a
upholstered valance with cord lock	1¾"	1¼"	2¼"	2½"	-¼ valance	-⅜" fabric	+1"
upholstered valance with continuous loop	2¼"	1¼"	2¾"	3"	-¼ valance	-⅜" fabric	+1"
top down bottom up with cord lock*	1¾"	1¼"	2¼"	2½"	-¼ valance	-⅜" fabric	+1"
2 on 1 headrail with cord lock*	1¾"	1¼"	2¼"	2½"	-¼ valance	-⅜" fabric	+1"
2 on 1 headrail with continuous loop*	2¼"	1¼"	2¾"	3"	-¼ valance	-⅜" fabric	+1"
SPECIAL REQUESTS							
minimized headrail - with cord lock	¾"	¾"	⅞"	2"	-⅜"		n/a
minimized headrail - with continous loop	1¾"	1"	1⅞"	2½"	-⅜"		n/a
standard style mount with cord lock or continuous loop*	2½"	1¼"	3"	3"	-¼ valance	-⅜" fabric	+1"

\* Automatically comes with an upholstered valance.     |     \*\* Add ⅛" - ¼" for heavier / thicker fabrics.

## Roller + Solar Shades

PRODUCT	DUSTBOARD SIZE		MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT**	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS (Bracket to Bracket)***	OM ADDITIONS
without valance	n/a		¾"	2¼"	2¼"	-⅝"	n/a
metal or fabric insert valance	n/a		1¼"	2¾"	1¼"	-⅝"	n/a
upholstered valance	IM 2½"	OM 3½"	1¼"	3"	3"	-⅜"	+1"
large metal or fabric insert valance*	n/a		1½"	4¼"	2¼"	-⅝"	n/a
large upholstered valance (inside mount)*	3"		1½"	3½"	n/a	-⅜"	n/a
* Large metal / upholstered valances may be required for thicker materials and oversized shades. Please contact customer service for details.					*** Roller / Solar shade fabrics will be approximately 1¼" narrower than your ordering width to allow for brackets. If concerned over resulting light gap please measure for outside mount.		
** Add ⅛" - ¼" for heavier / thicker fabrics.							

## Cordless Roller + Solar Shades

OPTION	SIZE LIMITATIONS	FABRIC DEDUCTION	MINIMUM DEPTH REQUIRED TO INSTALL	MINIMUM DEPTH REQUIRED FOR FLUSH MOUNT	MINIMUM DEPTH REQUIRED FOR OUTSIDE MOUNT
Rail	28"W - 34 ⅝"W x 50" L 35"W - 96" W x 96" L	¾"	1"	1⅞"	1⅞"
Metal Valance Medium	28"W - 34 ⅝"W x 50" L 35"W - 96" W x 96" L	¾"	1¼"	3⅝"	2"
Metal Valance Large	28"W - 34 ⅝"W x 50" L 35"W - 96" W x 96" L	¾"	1½"	4⅜"	2¼"
Upholstered Valance	28"W - 34 ⅝"W x 50" L 35"W - 96" W x 96" L	¾"	1¼"	3"	3"

## Bamboo + Grass Woven Wood Shades

PRODUCT	DUSTBOARD SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT**	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS	OM ADDITIONS
waterfall style with standard cord lock	1½"	⅝"	1¾"	1½"	-½"	n/a
waterfall style with continuous loop control	2½"	⅝"	2¾"	1½"	-½"	n/a
waterfall style with cordless control	2½"	¾"	2¾"	3"	-⅜"	n/a
standard style with standard cord lock	1½"	⅝"	1¾"	1½"	-½"	n/a
standard style with continuous loop control	2½"	⅝"	2¾"	1½"	-½"	n/a
SPECIAL REQUESTS						
minimized headrail (waterfall) with cord lock	¾"	⅝"	⅞"	2½"	-½"	n/a
minimized headrail (standard) with cord lock	¾"	⅝"	1¼"	2½"	-½"	n/a
Please Note: A minimized headrail is not available for continuous loop control.           ** Add ⅛" - ¼" for heavier / thicker fabrics.						

## Naturals Woven Wood Shades: Waterfall + Cascade Style

PRODUCT	DUSTBOARD SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT**	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS		OM ADDITIONS
with cord lock	1¾"	¾"	1⅞"	2½"	-⅜"		n/a
with continuous loop control	2¼"	1"	2⅜"	3"	-⅜"		n/a
upholstered valance with cord lock*	1¾"	1¼"	2¼"	2½"	-¼ valance	-⅜" fabric	+1"
upholstered valance with continuous loop*	2¼"	1¼"	2¾"	3"	-¼ valance	-⅜" fabric	+1"
top down bottom up with cord lock*	1¾"	1¼"	2¼"	2½"	-¼ valance	-⅜" fabric	+1"
2 on 1 headrail with cord lock*	1¾"	1¼"	2¼"	2½"	-¼ valance	-⅜" fabric	+1"
2 on 1 headrail with continuous loop*	2¼"	1¼"	2¾"	3"	-¼ valance	-⅜" fabric	+1"
SPECIAL REQUESTS							
minimized headrail - with cord lock	¾"	¾"	⅞"	2"	-⅜"		n/a
minimized headrail - with continuous loop	1¾"	1"	1⅞"	2½"	-⅜"		n/a
standard style mount with cord lock or continuous loop*	2½"	1¼"	3"	3"	-¼ valance	-⅜" fabric	+1"
* Automatically comes with an upholstered valance.      ** Add ⅛" - ¼" for heavier / thicker fabrics.							

## Naturals Woven Wood Shades: Standard Style\*

PRODUCT	DUSTBOARD SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT**	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS		OM ADDITIONS
with cord lock	2½"	1¼"	3"	3"	-¼ valance	-⅜" fabric	+1"
with continuous loop control	2½"	1¼"	3"	3"	-¼ valance	-⅜" fabric	+1"
upholstered valance with cord lock	2½"	1¼"	3"	3"	-¼ valance	-⅜" fabric	+1"
upholstered valance with continuous loop	2½"	1¼"	3"	3"	-¼ valance	-⅜" fabric	+1"
* Automatically comes with an upholstered valance.           ** Add ¼" - ½" for heavier / thicker fabrics.							

## Wood Blinds

PRODUCT	HEADRAIL SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT*	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS		OM ADDITIONS	
cord tilt + wand tilt	2½"	¾"	3"	1¾"	-¼ headrail	-½" slats	+⅜ headrail	+1" valance
* Includes standard wood valance.								

## Cellular Shades + XL Pleat Shades

PRODUCT	HEADRAIL SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS	OM ADDITIONS
with cord lock	2⅝"	⅝"	2⅝"	⅝"	-⅜"	n/a
with continuous loop	2¼"	⅞"	2¼"	1¾"	-⅜"	n/a
with top down bottom up	2⅝"	⅝"	2⅝"	⅝"	-⅜"	n/a
with cordless system	2¼"	⅞"	2¼"	1¾"	-⅜"	n/a

# MOUNTING REQUIREMENTS (CONTINUED)

## XL Vertical

PRODUCT	RAIL SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS	OM ADDITIONS
cord control	1½"	6"	10"	3½"	-½"	n/a

Please Note: Each vane is 9¼" width and a minimum depth of 10" is required for full rotation.

## Panel Systems

PRODUCT	RAIL SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS	OM ADDITIONS
3 channel track	2"	1¼"	2"	2"	-⅝"	n/a
4 channel track	2⅝"	2"	2¾"	2"	-⅝"	n/a
5 channel track	3¼"	2"	3⅝"	2"	-⅝"	n/a

Please Note: Widths of 48" - 84" will use a 3 channel track for both one way draw and split draw. Widths of 120½" - 180" will use a 5 channel track for one way draw and a 4 channel track for split draw. Widths of 84½" - 120" will use a 4 channel track for one way draw and a 3 channel track for split draw. Widths of 180½" - 220" will use a 5 channel track for one way draw and a 5 channel track for split draw.

## Cornices

PRODUCT	DUSTBOARD SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT*	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS	OM ADDITIONS
1½" clearance	1½"	1"	2"	2"	-¼	+1½"
2½" clearance	2½"	1½"	3"	3"	-¼	+1½"
3½" clearance	3½"	2"	4"	4"	-¼	+1½"
5½" clearance	5½"	2½"	6"	4½"	-¼	+1½"
7¼" clearance	7¼"	3"	7¾"	6"	-¼	+1½"

Please Note: Face will be ½" thick when cornice has nailheads. | \* Add ⅛" - ¼" for cornices with nailheads and / or welting. Add ⅛" - ¼" for heavier / thicker fabrics.

## Drapery Hardware (The Shade Store Only)

DECORATIVE COLLECTIONS	WALL MOUNT BRACKETS: All Pleat Styles Top of Pole to Top of Drapery	WALL MOUNT BRACKETS: Grommet Style Only Top of Pole to Top of Drapery	CEILING MOUNT BRACKETS: Pinch, Tailored, Ripple Fold Ceiling to Top of Drapery	CEILING MOUNT BRACKETS: Grommet Style Only Ceiling to Top of Drapery	WALL MOUNT BRACKET SINGLE SET: Top of Wall Bracket "Plate" to Top of Drapery (Grommet Not Included)	WALL MOUNT BRACKET DOUBLE SET: Top of Wall Bracket "Plate" to Top of Drapery (Grommet Not Included)
Steel Collection – 1⅝" Diameter	-2⅞"	+1"	-4¼"	-1¼"	-2½" *	- 2⅝" *
Gramercy Collection – 1⅝" Diameter	-2⅞"	+1"	-5"	-2 1/2"	-2¾" *	- 2⅞" *
Acero Collection – 1⅝" Diameter	-2"	+1"	-3¾"	-¾"	-1⅞" *	- 1⅞" *
Madison   Tribeca Collection – 1½" Diameter †	-1¼"	n/a	-1¾"	n/a	-2¼"	-2½"
Swarovski Collection – 1½" Diameter †	-1¼"	n/a	-1¾"	n/a	-2¼"	-2½"
Lexington Collection – 1½" Tall †	-1¾"	n/a	-2⅝"	n/a	-2½"	-2½"
Wrought Iron Collection – 1⅝" Diameter	-2⅞"	+1"	-3½"	-¾"	-3⅝"	n/a
Essex Collection – 1⅝" Diameter	-2½"	+1"	-3½"	-¼"	-2¼" *	n/a
Royal Wood Collection – 2" Diameter	-3¾"	n/a	n/a	n/a	-2⅞" *	n/a
Carnegie Collection – 1½" Diameter	-2¼"	n/a	n/a	n/a	-2½" *	n/a
Bowery   Lenox Collection – 1⅝" Diameter	-2⅞"	n/a	-5⅝"	n/a	-2⅞" *	n/a

† No rings come with this collection - deduct additional ⅛" for ripple fold drapery. | \* Allow ⅛" clearance when wall mounting a pole with rings to ceiling line so rings can move freely. Please Note: Standard returns are 4" deep on Shade Store drapery. Custom return sizes available upon request.

## Drapery Hardware (The Shade Store Only)

CUSTOM TRACKS	WALL MOUNT: Top of Track to Top of Drapery	CEILING MOUNT: Ceiling to Top of Drapery
Ripple Fold / Cubicle Track – ¾" Track	-1¼"	-1¼"
Custom Track – ¾" Track	-1¼"	-1¼"

Please Note: Standard returns are 4" deep on Shade Store drapery. Custom return sizes available upon request.

## Drapery Hardware (Room & Board Only)

DRAPERY HARDWARE	WALL MOUNT: Pinch, Tailored, Ripple Fold Top of Pole to Top of Drapery	WALL MOUNT: Grommet Top of Pole to Top of Drapery	CEILING MOUNT: Pinch, Tailored, Ripple Fold Ceiling to Top of Drapery	CEILING MOUNT: Grommet Ceiling to Top of Drapery	TOP OF WALL BRACKET "PLATE" TO TOP OF FABRIC
decorative hardware collection	- 2"	+1"	- 3⅝"	-½"	- 2⅞" *
rail collection – 1⅝" diameter (PP/TP)	-1¼"	n/a	-3"	n/a	- 2⅞"
rail collection – 1⅝" diameter (RF)	-1½"	n/a	-3¼"	n/a	- 2⅞"
custom track collection (PP/TP)	-1¼"	n/a	-1¼"	n/a	- 1¼"
custom track collection (RF)	-1¼"	n/a	-1¼"	n/a	- 1¼"

\* Allow ⅛" clearance when wall mounting a pole with rings to ceiling line so rings can move freely. Please Note: Wall mount bracket rises above pole ⅛" on decorative hardware and 1¼" on rail collection. Please Note: Standard returns are 4¾" deep on Room & Board drapery. Custom return sizes available upon request.