

THE SHADE STORE® MOUNTING REQUIREMENTS

Roman Shades (All Styles)

PRODUCT	DUSTBOARD SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT**	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS	OM ADDITIONS
with cord lock	1¼"	¾"	1½"	2½"	-¾"	n/a
with continuous loop control	2¼"	1"	2¾"	3"	-¾"	n/a
upholstered valance with cord lock	1¼"	1¼"	2¼"	2½"	-¼ valance -¾" fabric	+1"
upholstered valance with continuous loop	2¼"	1¼"	2¾"	3"	-¼ valance -¾" fabric	+1"
top down bottom up with cord lock*	1¼"	1¼"	2¼"	2½"	-¼ valance -¾" fabric	+1"
2 on 1 headrail with cord lock*	1¼"	1¼"	2¼"	2½"	-¼ valance -¾" fabric	+1"
2 on 1 headrail with continuous loop*	2¼"	1¼"	2¾"	3"	-¼ valance -¾" fabric	+1"
SPECIAL REQUESTS						
minimized headrail - with cord lock	¾"	¾"	¾"	2"	-¾"	n/a
minimized headrail - with continuous loop	1¼"	1"	1½"	2½"	-¾"	n/a
standard style mount with cord lock or continuous loop*	2½"	1¼"	3"	3"	-¼ valance -¾" fabric	+1"

* Automatically comes with an upholstered valance. | ** Add ¼" - ½" for heavier / thicker fabrics.

Roller + Solar Shades

PRODUCT	DUSTBOARD SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT**	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS (Bracket to Bracket)***	OM ADDITIONS
without valance	n/a	¾"	2¼"	2¼"	-½"	n/a
metal or fabric insert valance	n/a	1¼"	2¾"	1¼"	-¼"	n/a
upholstered valance	IM 2½" OM 3½"	1¼"	3"	3"	-¾"	+1"
large metal or fabric insert valance*	n/a	1½"	4¼"	2¼"	-½"	n/a
large upholstered valance (inside mount)*	3"	1½"	3½"	n/a	-¾"	n/a

* Large metal / upholstered valances may be required for thicker materials and oversized shades. Please contact customer service for details. | *** Roller / Solar shade fabrics will be approximately 1¼" narrower than your ordering width to allow for brackets. If concerned over resulting light gap please measure for outside mount.
** Add ¼" - ½" for heavier / thicker fabrics.

Cordless Roller + Solar Shades

OPTION	SIZE LIMITATIONS	FABRIC DEDUCTION	MINIMUM DEPTH REQUIRED TO INSTALL	MINIMUM DEPTH REQUIRED FOR FLUSH MOUNT	MINIMUM DEPTH REQUIRED FOR OUTSIDE MOUNT
Rail	28"W - 34 ¾"W x 50" L 35"W - 96" W x 96" L	¾"	1"	1½"	1½"
Metal Valance Medium	28"W - 34 ¾"W x 50" L 35"W - 96" W x 96" L	¾"	1¼"	3½"	2"
Metal Valance Large	28"W - 34 ¾"W x 50" L 35"W - 96" W x 96" L	¾"	1½"	4¾"	2½"
Upholstered Valance	28"W - 34 ¾"W x 50" L 35"W - 96" W x 96" L	¾"	1¼"	3"	3"

Bamboo + Grass Woven Wood Shades

PRODUCT	DUSTBOARD SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT**	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS	OM ADDITIONS
waterfall style with standard cord lock	1½"	¾"	1¾"	1½"	-½"	n/a
waterfall style with continuous loop control	2½"	¾"	2¾"	1½"	-½"	n/a
waterfall style with cordless control	2½"	¾"	2¾"	3"	-¾"	n/a
standard style with standard cord lock	1½"	¾"	1¾"	1½"	-½"	n/a
standard style with continuous loop control	2½"	¾"	2¾"	1½"	-½"	n/a
SPECIAL REQUESTS						
minimized headrail (waterfall) with cord lock	¾"	¾"	¾"	2½"	-½"	n/a
minimized headrail (standard) with cord lock	¾"	¾"	1¼"	2½"	-½"	n/a

Please Note: A minimized headrail is not available for continuous loop control. | ** Add ¼" - ½" for heavier / thicker fabrics.

Naturals Woven Wood Shades: Waterfall + Cascade Style

PRODUCT	DUSTBOARD SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT**	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS	OM ADDITIONS
with cord lock	1¼"	¾"	1½"	2½"	-¾"	n/a
with continuous loop control	2¼"	1"	2¾"	3"	-¾"	n/a
upholstered valance with cord lock*	1¼"	1¼"	2¼"	2½"	-¼ valance -¾" fabric	+1"
upholstered valance with continuous loop*	2¼"	1¼"	2¾"	3"	-¼ valance -¾" fabric	+1"
top down bottom up with cord lock*	1¼"	1¼"	2¼"	2½"	-¼ valance -¾" fabric	+1"
2 on 1 headrail with cord lock*	1¼"	1¼"	2¼"	2½"	-¼ valance -¾" fabric	+1"
2 on 1 headrail with continuous loop*	2¼"	1¼"	2¾"	3"	-¼ valance -¾" fabric	+1"
SPECIAL REQUESTS						
minimized headrail - with cord lock	¾"	¾"	¾"	2"	-¾"	n/a
minimized headrail - with continuous loop	1¼"	1"	1½"	2½"	-¾"	n/a
standard style mount with cord lock or continuous loop*	2½"	1¼"	3"	3"	-¼ valance -¾" fabric	+1"

* Automatically comes with an upholstered valance. | ** Add ¼" - ½" for heavier / thicker fabrics.

Naturals Woven Wood Shades: Standard Style*

PRODUCT	DUSTBOARD SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT**	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS	OM ADDITIONS
with cord lock	2½"	1¼"	3"	3"	-¼ valance -¾" fabric	+1"
with continuous loop control	2½"	1¼"	3"	3"	-¼ valance -¾" fabric	+1"
upholstered valance with cord lock	2½"	1¼"	3"	3"	-¼ valance -¾" fabric	+1"
upholstered valance with continuous loop	2½"	1¼"	3"	3"	-¼ valance -¾" fabric	+1"

* Automatically comes with an upholstered valance. | ** Add ¼" - ½" for heavier / thicker fabrics.

Wood Blinds

PRODUCT	HEADRAIL SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT*	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS	OM ADDITIONS
cord tilt + wand tilt	2½"	¾"	3"	1¼"	-¼ headrail -½" slats	+¾ headrail +1" valance

* Includes standard wood valance.

Cellular Shades + XL Pleat Shades

PRODUCT	HEADRAIL SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS	OM ADDITIONS
with cord lock	2¾"	¾"	2¾"	¾"	-¾"	n/a
with continuous loop	2¼"	¾"	2¼"	1¼"	-¾"	n/a
with top down bottom up	2¾"	¾"	2¾"	¾"	-¾"	n/a
with cordless system	2¼"	¾"	2¼"	1¼"	-¾"	n/a

MOUNTING REQUIREMENTS (CONTINUED)

XL Vertical

PRODUCT	RAIL SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS	OM ADDITIONS
cord control	1 7/8"	6"	10"	3 1/8"	-1/2"	n/a

Please Note: Each vane is 9 3/4" width and a minimum depth of 10" is required for full rotation.

Panel Systems

PRODUCT	RAIL SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS	OM ADDITIONS
3 channel track	2"	1 1/4"	2"	2"	-3/8"	n/a
4 channel track	2 3/8"	2"	2 3/4"	2"	-3/8"	n/a
5 channel track	3 1/4"	2"	3 3/8"	2"	-3/8"	n/a

Please Note: Widths of 48" - 84" will use a 3 channel track for both one way draw and split draw.

Widths of 84 1/2" - 120" will use a 4 channel track for one way draw and a 3 channel track for split draw.

Widths of 120 1/2" - 180" will use a 5 channel track for one way draw and a 4 channel track for split draw.

Widths of 180 1/2" - 220" will use a 5 channel track for one way draw and a 5 channel track for split draw.

Cornices

PRODUCT	DUSTBOARD SIZE	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT*	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	IM DEDUCTIONS	OM ADDITIONS
1 1/2" clearance	1 1/2"	1"	2"	2"	-1/4"	+1 1/2"
2 1/2" clearance	2 1/2"	1 1/2"	3"	3"	-1/4"	+1 1/2"
3 1/2" clearance	3 1/2"	2"	4"	4"	-1/4"	+1 1/2"
5 1/2" clearance	5 1/2"	2 1/2"	6"	4 1/2"	-1/4"	+1 1/2"
7 1/4" clearance	7 1/4"	3"	7 3/4"	6"	-1/4"	+1 1/2"

Please Note: Face will be 1/2" thick when cornice has nailheads.

* Add 1/8" - 1/4" for cornices with nailheads and / or welting. Add 1/8" - 1/4" for heavier / thicker fabrics.

Drapery Hardware Deductions (The Shade Store Only)

RF - Ripple Fold | TP - Tailored Pleat | PP - Pinch Pleat | GR - Grommet | IP - Inverted Pleat | GB - Goblet

TRACK SYSTEMS HARDWARE COLLECTION	WALL MOUNT BRACKETS: RF, TP, PP, IP, GB Top of Track to Top of Drapery	WALL MOUNT BRACKETS: GR Top of Track to Top of Drapery	CEILING MOUNT BRACKETS: RF, TP, PP, IP, GB Ceiling to Top of Drapery	CEILING MOUNT BRACKETS: GR Ceiling to Top of Drapery	WALL MOUNT BRACKET SINGLE SET: RF, TP, PP, IP, GB Top of Wall Bracket Plate to Top of Drapery	WALL MOUNT BRACKET DOUBLE SET: RF, TP, PP, IP, GB Top of Wall Bracket Plate to Top of Drapery
Madison/Tribeca Collection: 1 1/8" Diameter*	-1 3/8"	n/a	-2"	n/a	-2 1/4"	-2 3/8"
Madison/Tribeca/Swarovski - w/Ceiling Bracket	n/a	n/a	-3 3/8"	n/a	n/a	n/a
Swarovski Collection: 1 1/8" Diameter*	-1 3/8"	n/a	-2"	n/a	-2 1/4"	-2 3/8"
Lexington Collection: 1 1/8" Diameter*	-1 1/8"	n/a	-2 1/2"	n/a	-2 3/8"	-2 3/8"
Lexington Collection - w/Ceiling Bracket	n/a	n/a	-3 3/8"	n/a	n/a	n/a
Ripple Fold - 3/4" Track	-1"	n/a	-1 1/8"	n/a	-1 1/4"	-1 1/4"
Custom Track - 3/4" Track	-1"	n/a	-1 1/8"	n/a	-1 1/4"	-1 1/4"
Motorized Custom Track - TSS & Somfy	-1 1/4"	n/a	-1 1/2"	n/a	-1 3/4"	-1 1/4"

Please Note:

* No rings come with these collections - deduct additional 1/8" for Ripple Fold Drapery

Custom return sizes available as custom request

Standard returns are 4" on all drapery except Rod Pocket & Cubicle

After drapery deductions are taken, you need to round down to the nearest 1/4" for the final drapery length measurements.

Drapery Hardware Deductions (The Shade Store Only)

CU - Cubicle

TRACK SYSTEMS HARDWARE COLLECTION	WALL MOUNT BRACKETS: CU Top of Pole to Top of Drapery	CEILING MOUNT BRACKETS: CU Ceiling to Top of Drapery	WALL MOUNT BRACKET SINGLE SET: CU Top of Wall Bracket Plate to Top of Drapery	WALL MOUNT BRACKET DOUBLE SET: CU Top of Wall Bracket Plate to Top of Drapery
Madison/Tribeca Collection: 1 1/8" Diameter*	-1 1/4"	-1 1/8"	-2 1/8"	-2 1/2"
Madison/Tribeca/Swarovski - w/Ceiling Bracket	n/a	-3 1/4"	n/a	n/a
Swarovski Collection: 1 1/8" Diameter*	-1 1/4"	-1 1/8"	-2 1/8"	-1 3/8"
Lexington Collection: 1 1/8" Diameter*	-1 3/4"	-2 3/8"	-2 1/2"	-2 1/2"
Lexington Collection - w/Ceiling Bracket	n/a	-3 3/4"	n/a	n/a
Custom Track - 3/4" Track	-7/8"	-1 1/8"	-1 1/8"	-1 1/8"

Workroom Notes:

* No rings come with these collections - deduct additional 1/8" for Ripple Fold Drapery

Custom return sizes available as custom request

After drapery deductions are taken, you need to round down to the nearest 1/4" for the final drapery length measurements.

Drapery Hardware Deductions (The Shade Store Only)

TP - Tailored Pleat | PP - Pinch Pleat | GR - Grommet | IP - Inverted Pleat | GB - Goblet

RODS & RINGS HARDWARE COLLECTION	WALL MOUNT BRACKETS: TP, PP, IP, GB Top of Pole to Top of Drapery	WALL MOUNT BRACKETS: GR Top of Pole to Top of Drapery	CEILING MOUNT BRACKETS: TP, PP, IP, GB Ceiling to Top of Drapery	CEILING MOUNT BRACKETS: GR Ceiling to Top of Drapery	WALL MOUNT BRACKET SINGLE SET: TP, PP, IP, GB Top of Wall Bracket Plate to Top of Drapery	WALL MOUNT BRACKET DOUBLE SET: TP, PP, IP, GB Top of Wall Bracket Plate to Top of Drapery
Steel Collection: 1 3/16" Diameter	-2 3/16"	+1"	-5 1/16"	-1 3/16"	-2 3/16"***	-2 3/16"***
Gramercy Collection: 1 1/8" Diameter	-1 1/8"	+1"	-5 1/8"	-2 1/4"	-2 3/8"***	-2 3/8"***
Acero Collection: 1 3/16" Diameter	-2 1/16"	+1"	-3 13/16"	-3/4"	-2 1/16"***	-2 1/16"***
Wrought Iron Collection: 1 3/16" Diameter	-2 1/16"	+1"	-3 13/16"	-3/4"	-3 1/16"	-3 1/16"***
Essex Collection: 1 3/16" Diameter	-2 3/8"	+1"	-3 7/8"	-1/4"	-2 5/8"***	n/a
Royal Wood Collection: 2" Diameter	-3 1/4"	n/a	n/a	n/a	-3 3/4"***	n/a
Carnegie Collection 1 1/2" Diameter	-2 1/4"	n/a	n/a	n/a	-2 3/8"***	n/a
Bowery Collection: 1 3/8" Diameter	-2 3/8"	n/a	-5 3/8"	n/a	-3 1/8"***	n/a
Lenox Collection 1 3/8" Diameter	-2 1/2"	n/a	-5 1/4"	n/a	-3"	n/a

Workroom Notes:

**Allow 1/2" clearance when wall mounting a pole with rings to ceiling line so rings can move freely

Standard returns are 4" on all drapery except Rod Pocket & Cubicle

Custom return sizes available as custom request

Rod Pocket - Top of Drapery = top of pole. Allow 1/2"-1" extra in length due to length that will be lost when fabric is "gathered" onto the rod.

After drapery deductions are taken, you need to round down to the nearest 1/4" for the final drapery length measurements.