

THE SHADE STORE® MOUNTING REQUIREMENTS

Roller + Solar Shades

PRODUCT	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT**	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	INSIDE MOUNT WORKROOM DEDUCTIONS**	WORKROOM MATERIAL DEDUCTIONS**
Designer Bracket*	¾"	2¼"	2¼"	-½"	-1¼"
Upholstered Valance*	1¼"	3"	3"	-¾"	-1¼"
Medium Metal Valance*	1¼"	3¾"	2"	-½"	-1¼"
Large Metal Valance	1½"	4¾"	2¼"	-½"	-1¼"
Cordless	2"	2½"	1¾"	-¼"	-¾"
Cordless with Upholstered Valance	1¼"	3½"	3"	-¾"	-¾"
Cordless with Medium Metal Valance*	1¼"	3¾"	2"	-¼"	-¾"
Cordless with Large Metal Valance	1½"	4¾"	2¼"	-¼"	-¾"
Motorized (shades up to 144" wide)*	¾"	2¼"	1¾"	-½"	-1¾"
Motorized (shades 144½" - 156" wide)	3¼"	3½"	3½"	-½"	-2¼"
Motorized with Upholstered Valance (shades up to 144" wide)*	1¼"	3¼"	3"	-¾"	-1¾"
Motorized with Upholstered Valance (shades 144½"-156" wide)	2½"	4"	3"	-¾"	-2¾"
Motorized with Medium Metal Valance*	1¼"	3¾"	2"	-½"	-1¼"
Motorized with Large Metal Valance	1½"	4¾"	2¼"	-½"	-1¼"
Double Roller - Small Metal Valance*	1½"	2¾"	1¾"	-¼"	-1¾"
Double Roller - Large Metal Valance*	1¾"	3¾"	2¾"	-¼"	-1¾"

* Oversized shades and thicker materials may require larger brackets or valances. Please contact customer service for details.

** The workroom will make these adjustments to the ordering width to ensure your shades have the perfect fit.

Please Note: Upholstered valances on shades ordered as outside mount will come 1" wider than the ordered width to accommodate the returns on the valance.

Roman Shades (All Styles)

PRODUCT	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	INSIDE MOUNT WORKROOM DEDUCTIONS**
Cord Lock	¾"	1¾"	2½"	-¾"
Continuous Loop	1¼"	2¾"	3"	-¾"
Cord Lock with Upholstered Valance	1¼"	2¼"	2¼"	-¼" valance -¾" fabric
Continuous Loop with Upholstered Valance	1¼"	2¾"	3"	-¼" valance -¾" fabric
Top Down Bottom Up*	1¼"	1¼"	2½"	-¼" valance -¾" fabric
Cordless	1¼"	2½"	3¼"	-¾"
Cordless with Upholstered Valance	1¼"	3"	3"	-¼" valance -¾" fabric
Multiple on 1 with Cord Lock*	1¼"	2¼"	2½"	-¼" valance -¾" fabric
Multiple on 1 with Continuous Loop*	1¼"	2¾"	3"	-¼" valance -¾" fabric
Motorized	1¾"	3"	3½"	-¾"
Motorized with Upholstered Valance	1¾"	3½"	3½"	-¼" valance -¾" fabric

SPECIAL REQUESTS - Please contact customer service for details

Cord Lock with Minimized Headrail	¾"	¾"	2"	-¾"
Continuous Loop with Minimized Headrail	1"	1¾"	2½"	-¾"
Standard Style with Cord Lock or Continuous Loop*	1¼"	3"	3"	-¼" valance -¾" fabric

* Automatically comes with an upholstered valance.

** The workroom will make these adjustments to the ordering width to ensure your shades have the perfect fit.

Please Note: Upholstered valances on shades ordered as outside mount will come 1" wider than the ordered width to accommodate the returns on the valance.

Bamboo + Grass Woven Wood Shades

PRODUCT	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	INSIDE MOUNT WORKROOM DEDUCTIONS*
Cord Lock - Waterfall Style	¾"	1¾"	1¾"	-½"
Cord Lock - Standard Style	¾"	2"	1¾"	-½"
Continuous Loop - Waterfall Style	1¼"	2¾"	1¾"	-½"
Continuous Loop - Standard Style	1¼"	3"	1¾"	-½"
Top Down Bottom Up	¾"	1¾"	1¾"	-½"
Cordless - Waterfall Style	1¼"	2¾"	1¾"	-½"
Cordless - Standard Style	1¼"	3"	1¾"	-½"
Multiple on 1 with Cord Lock - Standard Style	¾"	2"	1¾"	-½"
Multiple on 1 with Continuous Loop - Standard Style	1¼"	3"	1¾"	-½"
Motorized - Waterfall Style	1¾"	3¾"	3¾"	-½"
Motorized - Standard Style	1¾"	3½"	3¾"	-½"

SPECIAL REQUESTS - Please contact customer service for details

Minimized Headrail with Cord Lock - Waterfall Style	¾"	1"	1¾"	-½"
Minimized Headrail with Continuous Loop - Waterfall Style	¾"	1¾"	1¾"	-½"
Minimized Headrail with Continuous Loop - Standard Style	¾"	2"	1¾"	-½"

* The workroom will make these adjustments to the ordering width to ensure your shades have the perfect fit.

Naturals Woven Wood Shades

PRODUCT	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	INSIDE MOUNT WORKROOM DEDUCTIONS**
Cord Lock - Waterfall & Cascade Styles	¾"	1¾"	2½"	-¾"
Cord Lock* - Standard Style	1¼"	3¼"	3¼"	-¼" valance -¾" fabric
Continuous Loop - Waterfall & Cascade Styles	1¼"	2¾"	3"	-¾"
Continuous Loop* - Standard Style	1¼"	3¼"	3¼"	-¼" valance -¾" fabric
Cord Lock with Upholstered Valance - Waterfall & Cascade Styles	1¼"	2¼"	2½"	-¼" valance -¾" fabric
Continuous Loop with Upholstered Valance - Waterfall & Cascade Styles	1¼"	2¾"	3"	-¼" valance -¾" fabric
Top Down Bottom Up*	1¼"	2¼"	2½"	-¼" valance -¾" fabric
Cordless - Waterfall & Cascade Styles	1¼"	2¾"	3"	-¾"
Cordless with Upholstered Valance - Waterfall & Cascade Styles	1¼"	3"	3"	-¼" valance -¾" fabric
Cordless* - Standard Style	1¼"	3¼"	3¼"	-¼" valance -¾" fabric
Multiple on 1 with Cord Lock* - Waterfall & Cascade Styles	1¼"	2¼"	2½"	-¼" valance -¾" fabric
Multiple on 1 with Cord Lock* - Standard Style	1¼"	3¼"	3¼"	-¼" valance -¾" fabric
Multiple on 1 with Continuous Loop* - Waterfall & Cascade Styles	1¼"	2¾"	3"	-¼" valance -¾" fabric
Multiple on 1 with Continuous Loop* - Standard Style	1¼"	3¼"	3¼"	-¼" valance -¾" fabric
Motorized - Waterfall & Cascade Styles	1¾"	3¾"	3¾"	-¾"
Motorized* - Standard Style	1¾"	3¾"	3¾"	-¼" valance -¾" fabric
Motorized with Upholstered Valance - Waterfall & Cascade Styles	1¾"	3½"	3¾"	-¼" valance -¾" fabric
Motorized with Upholstered Valance* - Standard Style	1¾"	3¾"	3¾"	-¼" valance -¾" fabric

SPECIAL REQUESTS - Please contact customer service for details

Cord Lock with Minimized Headrail	¾"	¾"	2"	-¾"
Continuous Loop with Minimized Headrail	1"	1¾"	2½"	-¾"

* Automatically comes with an upholstered valance.

** The workroom will make these adjustments to the ordering width to ensure your shades have the perfect fit.

Please Note: Upholstered valances on shades ordered as outside mount will come 1" wider than the ordered width to accommodate the returns on the valance.

Wood Blinds + Metal Blinds

PRODUCT	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT*	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	INSIDE MOUNT WORKROOM DEDUCTIONS**	OUTSIDE MOUNT ADDITIONS**
2" Metal Blinds	¾"	2¾"	1¾"	-½" headrail -½" slats	+ ¾" headrail +1" valance
1" Metal Blinds	¾"	2¼"	1¾"	-½" headrail -½" slats	+ ¾" headrail +1" valance
Basics, Painted, Bamboo, Laminated, High Gloss, & Exotic	¾"	2¾"	1¾"	-½" headrail -½" slats	+ ¾" headrail +1" valance
Faux Wood	¾"	3"	1¾"	-½" headrail -½" slats	+ ¾" headrail +1" valance

* Includes standard wood valance

** The workroom will make these adjustments to the ordering width to ensure your shades have the perfect fit.

MOUNTING REQUIREMENTS (CONTINUED)

Cellular Shades + Pleated Shades

PRODUCT	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	INSIDE MOUNT WORKROOM DEDUCTIONS*
Cord Lock	5/8"	2 3/8"	5/8"	-3/8"
Continuous Loop	7/8"	2 1/4"	1 3/4"	-3/8"
Top Down Bottom Up	5/8"	2 3/8"	5/8"	-3/8"
Day/Night - Cord Lock	5/8"	2 3/8"	5/8"	-3/8"
Day/Night - Cordless	7/8"	2 1/4"	1 3/4"	-3/8"
Cordless	7/8"	2 1/4"	1 3/4"	-3/8"
Multiple on 1 with Cord Lock	5/8"	2 3/8"	5/8"	-3/8"
Multiple on 1 with Continuous Loop	7/8"	2 1/4"	1 3/4"	-3/8"
Motorized - Battery Motor	1 1/4"	2 1/4"	1 3/4"	-3/8"
Motorized - Plug-In Motor	1 1/2"	2 3/4"	1 3/4"	-3/8"

* The workroom will make these adjustments to the ordering width to ensure your shades have the perfect fit.

Panel Track Blinds

COVERAGE WIDTH	DRAW TYPE	NUMBER OF CHANNELS	NUMBER OF PANELS	MINIMUM DEPTH REQUIRED FOR SECURE IM	MINIMUM DEPTH REQUIRED FOR FLUSH IM	MINIMUM SPACE REQUIRED FOR OM	IM WORKROOM DEDUCTIONS*
Up to 84"	One Way	3	3	1 1/4"	2 1/2"	2"	-3/8"
	Center Open	3	4	1 1/4"	2 1/2"	2"	-3/8"
84 1/2" - 120"	One Way	4	4	2"	2 3/4"	2"	-3/8"
	Center Open	3	4	1 1/4"	2 1/2"	2"	-3/8"
120 1/2" - 180"	One Way	5	5	2"	3 3/8"	2"	-3/8"
	Center Open	4	6	2"	2 3/4"	2"	-3/8"
180 1/2" - 216"	One Way	5	5	2"	3 3/8"	2"	-3/8"
	Center Open	5	8	2"	3 3/8"	2"	-3/8"

XL Vertical Blinds

PRODUCT	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	INSIDE MOUNT WORKROOM DEDUCTIONS*
All Styles	6"	10"	3 3/8"	-1/2"

* The workroom will make these adjustments to the ordering width to ensure your shades have the perfect fit. Please Note: Each vane is 9 3/4" wide and a minimum depth of 10" is required for full rotation.

Cornices

PRODUCT	MINIMUM DEPTH REQUIRED FOR SECURE INSIDE MOUNT	MINIMUM DEPTH REQUIRED FOR FLUSH INSIDE MOUNT*	MINIMUM SPACE REQUIRED FOR OUTSIDE MOUNT	INSIDE MOUNT WORKROOM DEDUCTIONS**
1 1/2" clearance	1"	2"	2"	-1/4"
2 1/2" clearance	1 1/2"	3"	3"	-1/4"
3 1/2" clearance	2"	4"	4"	-1/4"
5 1/2" clearance	2 1/2"	6"	4 1/2"	-1/4"
7 1/4" clearance	3"	7 3/4"	6"	-1/4"

* Add 1/8" - 1/4" for cornices with nailheads and / or welting. Add 1/8" - 1/4" for heavier / thicker fabrics.

** The workroom will make these adjustments to the ordering width to ensure your shades have the perfect fit.

Please Note: Face will be 1/2" thick when cornice has nailheads.

Cornices ordered as outside mount will come 1 1/2" wider than the ordered width to accommodate the returns on the cornice.

Drapery Hardware Deductions

RF - Ripple Fold | TP - Tailored Pleat | PP - Pinch Pleat | IP - Inverted Pleat | GB - Goblet

TRACK SYSTEMS HARDWARE COLLECTION	WALL MOUNT BRACKETS RF, TP, PP, IP, GB Top of Track to Top of Drapery	CEILING MOUNT BRACKETS RF, TP, PP, IP, GB Ceiling to Top of Drapery	WALL MOUNT BRACKET SINGLE SET RF, TP, PP, IP, GB Top of Wall Bracket Plate to Top of Drapery	WALL MOUNT BRACKET DOUBLE SET RF, TP, PP, IP, GB Top of Wall Bracket Plate to Top of Drapery
Madison/Tribeca Collection: 1 1/8" Diameter	-1 3/8"	-2"	-2 1/4"	-2 3/4"
Swarovski Collection: 1 1/8" Diameter	-1 3/8"	-2"	-2 1/4"	-2 3/4"
Lexington Collection: 1 3/8" Diameter	-1 7/8"	-2 1/2"	-2 3/8"	-2 5/8"
Lincoln Track - 1" Square	-1 1/4"	-1 1/2"	-2 1/2"	-2 1/2"
Custom Track - 3/4" Track	-1"	-1 1/8"	-1 1/4"	-1 1/4"
Motorized Custom Track	-1 1/4"	-1 1/2"	-1 3/4"	-1 3/4"

SPECIAL REQUESTS - Please contact customer service for details

Madison/Tribeca/Swarovski - w/Extension Ceiling Bracket	N/A	-3 3/8"	N/A	N/A
Lexington Collection - w/Extension Ceiling Bracket	N/A	-3 3/8"	N/A	N/A
Lincoln Track - w/Extension Ceiling Bracket	N/A	-3 3/8"	N/A	N/A

Standard returns are 4" on all drapery except Rod Pocket & Cubicle - Custom return sizes available as custom request. Please contact customer service for details. After drapery deductions are taken, round down to the nearest 1/4" for the final drapery length measurements.

Drapery Hardware Deductions

CU - Cubicle

TRACK SYSTEMS HARDWARE COLLECTION	WALL MOUNT BRACKETS CU Top of Track to Top of Drapery	CEILING MOUNT BRACKETS CU Ceiling to Top of Drapery	WALL MOUNT BRACKET SINGLE SET CU Top of Wall Bracket Plate to Top of Drapery	WALL MOUNT BRACKET DOUBLE SET CU Top of Wall Bracket Plate to Top of Drapery
Madison/Tribeca Collection: 1 1/8" Diameter	-1 1/4"	-1 1/8"	-2 1/2"	-2 1/2"
Swarovski Collection: 1 1/8" Diameter	-1 1/4"	-1 7/8"	-2 1/8"	-1 7/8"
Lexington Collection: 1 3/8" Diameter	-1 3/4"	-2 3/8"	-2 1/2"	-2 1/2"
Lincoln Track - 1" Square	-1 1/4"	-1 1/8"	-2 1/2"	-2 1/8"
Custom Track - 3/4" Track	-7/8"	-1 1/8"	-1 1/8"	-1 1/8"

SPECIAL REQUESTS - Please contact customer service for details

Madison/Tribeca/Swarovski - w/Extension Ceiling Bracket	N/A	-3 1/4"	N/A	N/A
Lexington Collection - w/Extension Ceiling Bracket	N/A	-3 3/4"	N/A	N/A
Lincoln Track - w/Extension Ceiling Bracket	N/A	-2 1/2"	N/A	N/A

Standard returns are 4" on all drapery except Rod Pocket & Cubicle - Custom return sizes available as custom request. Please contact customer service for details. After drapery deductions are taken, round down to the nearest 1/4" for the final drapery length measurements.

Drapery Hardware Deductions

TP - Tailored Pleat | PP - Pinch Pleat | IP - Inverted Pleat | GB - Goblet | GR - Grommet | RP - Rod Pocket*

RODS & RINGS HARDWARE COLLECTION	WALL MOUNT BRACKETS: TP, PP, IP, GB Top of Pole to Top of Drapery	WALL MOUNT BRACKETS: GR Top of Pole to Top of Drapery	CEILING MOUNT BRACKETS: TP, PP, IP, GB Ceiling to Top of Drapery	CEILING MOUNT BRACKETS: GR Ceiling to Top of Drapery	WALL MOUNT BRACKET SINGLE SET: TP, PP, IP, GB Top of Wall Bracket Plate to Top of Drapery	WALL MOUNT BRACKET DOUBLE SET: TP, PP, IP, GB Top of Wall Bracket Plate to Top of Drapery
Steel Collection: 1 3/16" Diameter	-2 1/4"	+1"	-5 1/4"	-1 1/8"	-2 5/8"	-2 5/8"
Gramercy Collection: 1 1/8" Diameter	-1 7/8"	+1"	-5 1/4"	-2 1/4"	-2 5/8"	-2 5/8"
Acero Collection: 1 3/16" Diameter	-2 1/8"	+1"	-3 3/8"	-3/4"	-2 1/2"	-2 1/2"
Wrought Iron Collection: 1 3/16" Diameter	-2 1/8"	+1"	-3 3/8"	-3/4"	-3 1/2"	-3 1/2"
Essex Collection: 1 3/16" Diameter	-2 3/8"	+1"	-3 3/8"	-1/4"	-2 5/8"	N/A
Royal Wood Collection: 2" Diameter	-3 1/4"	N/A	N/A	N/A	-3 3/4"	N/A
Carnegie Collection 1 1/2" Diameter	-2 1/4"	N/A	N/A	N/A	-2 5/8"	N/A
Bowery Collection: 1 3/8" Diameter	-2 3/8"	N/A	-5 3/8"	N/A	-3 1/8"	N/A
Lenox Collection 1 3/8" Diameter	-2 1/4"	N/A	-5 1/4"	N/A	-3"	N/A

*Rod Pocket: Top of Drapery = Top of Pole. Add 1/2" - 1" extra in length due to length lost when fabric is "gathered" onto the rod.

**Allow 1/2" clearance from ceiling when wall mounting a pole with rings so rings can move freely

Standard returns are 4" on all drapery except Rod Pocket & Cubicle - Custom return sizes available as custom request. Please contact customer service for details. After drapery deductions are taken, round down to the nearest 1/4" for the final drapery length measurements.